

**I-4210**



The Datamax I-4210 brings integrated application computing power to the I-Class family of industrial barcode label printers with the addition of the MCL Client from MCL Technologies. MCL, or Macro Command Language, is a completely integrated application development suite tuned for the demands of data collection applications. After developing an application on an MCL development computer the application project is uploaded to the I-4210 where it is hosted as a self-sufficient application. The development computer is no longer necessary for the application to run and the MCL-enabled I-4210 can interact with printer-resident look-up tables as well as wired and wirelessly connected remote ERP systems or other host databases.

The I-4210 retains the standardized I-Class engineering and features such as a precision-crafted die-cast aluminum frame, a 32-bit processor with 8 or 16 MB of standard memory, a front panel user interface with color-coded cues for operator control, an embossed loading diagram for media and ribbon, a unique collapsible ribbon hub and wide-access print mechanism for effortless loading, and a user accessible card cage for the addition of various connectivity option cards.

For more sophisticated MCL applications, additional connectivity and/or input devices may be required. To accommodate these circumstances Datamax has also made available the following items:

- **RS-232 Dual Serial Port Adapter Cable**  
*This cable allows two separate external serial devices to share an I-Class serial port for MCL applications that might require, for example, both a barcode scanner and a weight scale; or a barcode scanner and a PS/2 keyboard.*
- **PS/2 Keyboard Serial Port Adapter Cable**  
*This cable allows a standard PS/2 QWERTY keyboard to be attached to the I-Class serial port, or dual serial port adapter cable, to provide the ability to interact with an MCL application via full-size keyboard.*

The I-4210 is ideal for a wide array of mission critical data collection and bar code labeling applications found in industries such as government, healthcare, food services, manufacturing, warehousing, distribution, and shipping.

When you need more from your industrial label printer than labels, step up to the Datamax MCL-enabled I-4210.



**Corporate Headquarters**  
4501 Parkway  
Commerce Boulevard  
Orlando, Florida USA 32808  
(407) 578-8007  
Fax (407) 578-8377  
<http://www.datamaxcorp.com>

**Datamax International**  
Herbert House  
Elizabeth Way, Pinnacles  
Harlow, Essex CM19 5FE UK  
+44 1279 772200  
Fax +44 1279 424448

**Datamax Latin America**  
4501 Parkway  
Commerce Boulevard  
Orlando, Florida USA 32808  
(407) 523-5520  
Fax (407) 578-8377

**Datamax Asia-Pacific Rep. Ofc.**  
19 Loyang Way  
#01-01 CILC Building  
Singapore 508724  
+65 542-2611  
Fax +65 542-3611

<b>PRINT SPEED</b>	10 IPS
<b>RESOLUTION</b>	203 DPI
<b>PRINT WIDTH</b>	4.10" (104 mm)
<b>PRINT LENGTH*</b>	0.25" – 99" (6.35mm – 2475.6mm) * Print length values vary with printer configuration
<b>MEMORY</b>	2MB Flash; 16MB SDRAM
<b>PRINTER TYPE</b>	Direct Thermal, Optional Thermal Transfer
<b>BAR CODE MODULUS</b>	5 mil to 150 mil (203 dpi); 3.3 mil to 150 mil (300 dpi); 2.5 mil to 150 mil (406 dpi); 1.6 mil to 150 mil (600 dpi) "X" dimension in picket fence or ladder orientations
<b>MEDIA WIDTH</b>	1" – 4.65" (25.4mm – 118.11mm)
<b>MEDIA TYPE</b>	Roll-fed or fan-fold materials, die-cut or continuous labels; perforated or continuous tag/ticket stock
<b>MEDIA THICKNESS</b>	.0025" – .0100" (.0635mm – .254mm)
<b>MEDIA SENSING</b>	Adjustable sensor detects "see through" for liner-backed die-cut labels and tags or reflective sensing for media with black stripe sensing
<b>SUPPLY ROLL</b>	8" (203mm) maximum diameter on 1.5" – 3" (38mm – 76mm) core. Fan-fold stock accepted from rear of printer
<b>REVOLVING MEDIA HUBS</b>	Standard 3" and 1.5" hubs, optional 40mm
<b>LABEL BACKFEED</b>	For use with optional cutter
<b>RIBBONS</b>	Industry standard ribbon widths; 1" (25mm) ribbon core, 1968' (600M) in length
<b>CABINET</b>	Metal construction, clear side window to easily monitor media supply levels
<b>BAR CODES</b>	Code 3 of 9, UPC-A, UPC-E, Interleaved 2 of 5, Code 128, EAN-8, EAN-13, HIBC, Codabar, Plessey, UPC 2 and 5 digit addendums, Code 93, Postnet, UCC/EAN Code 128, Telepen, UPS MaxiCode, FIM, PDF417, USD-8, Datamatrix, QR Code, Aztec, TLC 39, Micro PDF417, RSS
<b>RESIDENT FONTS</b>	Ten alphanumeric fonts from .035" (.89mm) to .64" (16.26mm) including OCR-A, OCR-B, CG Triumvirate™, CG Triumvirate Bold Condensed™ scalable font from AGFA®.
<b>DOWNLOADABLE FONT TYPES</b>	True-Type, AGFA® Intellifont™, Bitmap
<b>CHARACTER SET</b>	Modified IBM® Code Page 850; includes characters for English and most European, Scandinavian and Spanish speaking countries
<b>FONT EXPANSION/ROTATION</b>	All fonts expandable vertically and horizontally up to 24x; fonts and graphics can be printed in four directions: 0°, 90°, 180° and 270°
<b>GRAPHICS SUPPORTED</b>	.PCX, .BMP and .IMG files
<b>REVERSE FIELDS/MIRROR IMAGE</b>	Any font or graphic field can be printed as a normal or reverse image
<b>INTERFACES</b>	Centronics® Parallel port, IEEE 1284 compliant and RS232 at 2,400 to 38,400 BPS; optional Ethernet, USB, and Twinax/Coax
<b>WINDOWS® DRIVER</b>	Used for creating label formats using virtually any Windows®-based program. Included on Datamax Accessories CD, or via our web site at <a href="http://www.datamaxcorp.com">www.datamaxcorp.com</a>
<b>POWER SOURCE</b>	Auto-sensing 90 – 204 VAC @ 47 – 63 Hz; specify appropriate power cord when ordering
<b>OPERATING TEMPERATURE</b>	32°F to 100°F (0°C to 38°C)
<b>DIMENSIONS</b>	12.70" H x 12.62" W x 18.60" D (322.6mm H x 320.6mm W x 472.5mm D)
<b>WEIGHT</b>	45 lbs., 20.5Kg

## DATAMAX I-CLASS OPTIONS:

- THERMAL TRANSFER
- LIGHT DUTY CUTTER
- STANDARD CUTTER
- INTERNAL REWIND
- LABEL PRESENT SENSOR
- DUAL SERIAL PORT "Y" CABLE
- PEEL AND PRESENT
- FONT EXPANSION CARD
- ILPC - CG TIMES™ FIRMWARE
- I/O EXPANSION CARD
- LINEAR SCANNER
- PS/2 KEYBOARD ADAPTER CABLE
- DMXNet ETHERNET CONNECTIVITY
- USB INTERFACE
- RS-422 INTERFACE
- TWINAX / COAX INTERFACE
- HANGUL, SIMPLIFIED CHINESE, AND KANJI FONT SUPPORT
- DMXrINET WIRELESS ETHERNET CONNECTIVITY



Built to UL, CSA and TUV-GS safety standards, FCC Class A emissions standard and CE Mark. This data sheet is for informational purposes only. DATAMAX MAKES NO WARRANTIES, EXPRESSED OR IMPLIED IN THIS SUMMARY. Specifications are subject to change without notice. All trademarks are the property of their respective owners. ©2003 DATAMAX BAR CODE PRODUCTS CORPORATION. All rights reserved. Datamax is an ISO 9001 registered company.