



The Most Reliable Portable Printers®

A DOVER COMPANY

## LP3™ Wireless Portable Thermal Label Printer

The retail floor is no place for downtime. Constantly reloading labels or paper, or getting a flashing low battery light in the middle of a markdown is simply unacceptable.

The LP3 3" wireless portable label printer from O'Neil delivers greater paper capacity, longer battery life and a range of wireless connectivity options for the retail and manufacturing marketplace. And of course, the reliability O'Neil is known for around the globe.

**Greater Paper Capacity.** The LP3 offers almost twice the paper capacity of any printer in its class. It prints from 1" to 3" label stock and can accommodate a wide variety of labels and paper, including the heavy stock necessary for hang tags and other specialty label needs. The LP3's side-load design allows for the fastest and easiest paper loading of any printer on the market. Users simply slide the roll into the printer, pop on the end-cap, and the paper is loaded quickly and trouble-free.

**Greater Battery Power.** The LP3 uses two standard 7.2V Lithium-Ion (Li-Ion), 2200 mAh rechargeable batteries, providing twice the power capacity available from competitive printers and eliminates the need for constant recharging between applications and in the middle of shifts. This is important for all applications and especially critical for battery-intensive wireless environments.

**Built-In Battery Charging.** When it comes to batteries and battery charging, the LP3 offers yet another significant benefit. Competitive printers use

expensive proprietary batteries, incorporating the electronics or "intelligence" necessary for quick-charging into the battery itself. The electronics for quick charging in the LP3 are built-in to the printer, not the battery, eliminating the need to purchase a substantially higher-priced battery or recharging station. Since all rechargeable batteries have a limited life and must be replaced, this becomes a considerable recurring cost and unnecessary expense to the user. The only accessory required for charging the LP3 is a low cost AC adapter.

**Complete Line of Media and Supplies.** O'Neil offers a complete line of supplies for the LP3. Our Certified Label Supply Program ensures optimum, trouble-free performance from the LP3 and guarantees the highest quality print output and image stability. Choose from in-stock labels or customize media to your specifications.

**Rugged and Reliable.** With uncompromising standards, the LP3 is engineered throughout to endure even the most punishing portable applications. It can take all the bumps and knocks inherent in the mobile workplace by withstanding multiple 4' drops to concrete.

**Two Year Warranty.** The LP3's rock-solid print mechanism is proven to provide years of service where other printers fail. The full two-year warranty, even on the printhead, offers peace of mind with our proven promise to stand behind every product we sell.



***"The new LP3 3" wireless portable label printer from O'Neil Product Development meets the requirements for the retail and manufacturing marketplace by providing almost twice the paper capacity and twice the battery power of comparable printers as well as a full range of wireless printing capabilities."***

Vertical Systems Reseller

### ▶ Unmatched Wireless Printing

The LP3's wireless capabilities allow retail environments to leverage their significant investment in existing infrastructure by offering a variety of wireless connectivity options. The LP3 is available with an optional built-in 802.11b/g or integrated Bluetooth® version 1.2 compliant module.



# Standard Features at a Glance

- Optional 802.11b/g or Bluetooth® networking technologies.
- Twice the paper and battery capacity of competitive label printers.
- Label presenter for quick and easy peel-and-apply.
- Comes with the industry's only standard two-year warranty - twice that of the competition!
- Accommodates variable media (1" to 3") including lined labels, paper and hang tags.
- Supports the printing of 1D bar codes and 2D symbologies.
- Supports international character sets, graphics and any Bitstream® bitmap font\*\*.
- Easily transported by durable hand or shoulder strap.
- Powered by two 2200 mAh-capacity Lithium Ion (Li-Ion) batteries with an optional AC adapter or cigarette lighter adapter for recharging.



**LP3™**

## Specification Highlights LP3™ Portable Thermal Label Printer

Physical Characteristics		
Dimensions	6.2" x 5.17" x 7.86" (157.5 x 131.3 x 199.6 mm)	
Weight (printer only)	39.9 oz (1.13 kg)	
Weight (w/ batteries & paper roll)	63.5 oz (1.80 kg)	
Drop Specification	4 ft (1.22 m)	
User Environment		
Operating Temperature	-4° F to 113° F (0° C to 45° C)	
Storage Temperature	-40° F to 158° F (-40° C to 70° C)	
Charging Temperature	41° F to 104° F (5° C to 40° C)	
Relative Humidity	10% to 90% non-condensing	
ESD Protection	8 kV Air, 4 kV Contact	
Communications		
<b>Serial</b>	RS-232; 460.8 kbps	
<b>802.11b/g</b>		
Frequency Band	2.4 to 2.4897 GHz	
Data Rates	Standard 802.11b/g rates	
Network Standard	IEEE 802.11b/g	
Wireless Access Modes	Infrastructure and ad hoc	
Wireless Medium	Direct Sequence Spread Spectrum (DSSS)	
Authentication	Open or Shared key	
Security Protocols	40 bit WEP, 128 bit WEP, WPA, LEAP, EAP-FAST, plus others available	
Network Support	DHCP	
Remote Management Support	Compatible with the O'Neil Printer Management Console and other remote management systems	
<b>Bluetooth®</b>		
Network Environment	Ad hoc or piconet network environments	
Supported Versions	v1.2 (compatible with v1.1 devices)	
Print Technology		
Printhead	Direct thermal, 203 dots per inch (8 dots per mm), 2.84" (72 mm) print width	
Printhead Warranty	2 years*	
Print Mechanism Speed	2" per second (51 mm per second)	
Media		
Type	<b>Labels</b> <b>Paper</b>	0.75" - 3" lined labels w/ Q-mark or gap sensing Direct thermal receipt paper (standard, premium, heavy duty, long-life, image protect, hi-temp, and all weather), synthetic media, UV coated media
	<b>Hang Tags</b>	2" hang tags
For optimum print quality & printer performance, use Certified O'Neil supplies.		
Capacity	3.5" (88.9 mm) maximum roll diameter (O.D.) 1" (25.4 mm) I.D. core	
Roll Width	1" - 3" (25.4 mm - 76.2 mm)	
Thickness	0.002" (0.05 mm) minimum 0.007" (0.18 mm) maximum	



Barcode-IT  
Horrocksford Offices  
Clitheroe Road  
Chatburn  
Lancashire  
BB7 4LA

Tel: 01200 441977  
Fax: 01200 440250

Web: [www.barcode-it.co.uk](http://www.barcode-it.co.uk)  
E-mail: [sales@barcode-it.co.uk](mailto:sales@barcode-it.co.uk)

Power Source		
Batteries	(2) 7.2V Lithium-Ion (Li-Ion), 2200 mAh (for a total of 4400 mAh)	
DC Input	12-15V, built-in spike and surge protection	
Endurance	<b>802.11b/g</b> <b>Bluetooth</b>	Prints approx. 1095 - 3" x 2.5" labels on a single battery charge (18.3 hours) Prints approx. 1674 - 3" x 2.5" labels on a single battery charge (26.7 hours)
Recharging	4-5 hours from AC adapter or cigarette lighter adapter LED indicator for charging status	
Fonts & Languages		
Memory Capacity	Flash Memory: 4 MBytes Ram Memory: 2 MBytes	
Standard Fonts	5.5CPI, 7.2CPI, 10.7CPI, 18.5CPI 20.4CPI & 22.6CPI (additional fonts available)	
Optional Characters	Arabic, Asian (incl Big 5, Simplified Chinese and Shift JIS), Greek, Hebrew, OCR-A, OCR-B, Unicode subset including Latin & Thai (additional international characters available)	
Bar Codes	<b>Linear</b> <b>2D symbologies</b>	Codabar, Code 39, Code 93, Code 128, EAN-8, EAN-13, Interleaved 2 of 5, MSI/Plessey, UCC/EAN-128, UPC-A, UPC-E AZTEC, PDF417, QR
Graphics	Supports storage of graphics/logos in Flash memory and transient "print once" graphics	
Software		
Protocol	Line Printer Mode, Easy Print®	
Device Management	O'Neil Printer Management Console (OPMC)	
Drivers	Windows CE and Desktop	
Label Designers	NiceLabel, BarTender®, DP Designer	
Software Development Kit	BlackBerry	
Agency Approvals		
FCC B, CE, UL/cUL		
Warranty		
2 years (including printer case and printhead*)		
Options / Accessories		
<ul style="list-style-type: none"> <li>• AC Adapter</li> <li>• Cigarette Lighter Adapter</li> <li>• Cleaning Cards and Kits</li> <li>• Data Cables for Hand-Held Devices</li> <li>• DB9 F Download</li> <li>• Dual External Battery Charger</li> <li>• Paper/Labels</li> <li>• Shoulder Strap</li> <li>• Spare Batteries</li> </ul>		

\* When used with approved media grades.  
\*\* Contact Technical Support for more information.

Specifications are subject to change without notice.

LP3™ and Easy Print® are trademarks of O'Neil Product Development, Inc. All other product and company names are trademarks, service marks or registered trademarks of their respective owners.

Copyright 2007, O'Neil Product Development, Inc.  
rev. 7/07 Made in the U.S.A.

