



# PV4

A compact and powerful  
mobile printer



# PV4 Mobile Printer.

Designed for powerful on-demand labelling across a diverse range of industries.

With the demand for cloud-enabled technology increasing year-on-year, businesses now seek IOT devices to deliver more than just the essentials in label printing. Next-generation solutions from SATO are designed to improve customer satisfaction, enhance productivity and provide a consistently accurate track and trace service for peace of mind.

That's why we are proud to introduce the PV4, a high-performing mobile printer engineered to meet the requirements of on-demand label printing environments.



## Logistics

**Enhance efficiency across all aspects of the supply chain**

Labels required through the supply chain including goods receipt, racks, and returned goods labels, can be printed efficiently by the PV4. It comes with major competitive emulations for seamless integration into existing workflows.



## Manufacturing

**Product labelling for enhance traceability and efficiency**

Built for tough industrial conditions, the PV4 mobile printer helps manufacturers gain clear visibility and traceability from raw materials to finished products, which is especially valuable in the event of a product defect. It has a durable polycarbonate body and rubber over-molded edges that absorb the force of an impact, a vital attribute in the manufacturing environment.

## Key Applications



## Retail

**Deliver efficient and simple on-demand printing to the shop floor where speed is key**

The PV4 makes label printing on a busy shop floor simple and efficient in crucial applications such as ad-hoc price changes and discounts, stock taking, and goods return labelling. It also enables retail workers to connect wirelessly at the point of sale to synchronise label prices in real-time to boost pricing accuracy and customer satisfaction.



## Healthcare

**Improve accuracy and efficiency to ensure the safety and satisfaction of patients**

From patient registration, lab tracking and asset management in healthcare facilities to the manufacturing, dispensing and distribution of pharmaceutical products, this next generation intelligent printer delivers accuracy and efficiency for users, enhancing safety of patients and consumers.





## Key Features



Achieve all your on-demand printing needs with one complete dynamic solution

### Simple Operation

An intuitive user experience with a simple and easy to use screen and menu layout



### Integrate and Connect

- The SATO PV4 printer has exceptional compatibility. Third-party emulations including **SLCS**, **BPL-Z™** and **BPL-C™** ensure it is a simple process to replace existing printers without creating complex new workflows and enables simple integration for IT departments.
- In addition, connectivity options such as **WiFi**, **Bluetooth 4.1**, **USB 2.0**, **NFC support**, **Android** and **iOS** compatibility offer an enhanced user experience.



### Compact and Robust Design

The PV4 complies with IP54 standard and combines compact design with robust construction. With a 1.8m (5.9 feet) drop resistance, it has a durable polycarbonate body and rubber over-molded edges to absorb the force of impact if dropped.

This innovative design helps prevent downtime due to breakage in both the internal and external workplace environment.

### Technical Tools

- iOS SDK, Android SDK, Windows SDK (Windows 10), Linux SDK
- Supported Drivers: Windows Driver (Euro Plus/Seagul) Linux CUPS Driver, Mac CUPS Driver, OPOS Driver
- Utility Program (Unified Label Utility, Net Configuration Tool) Label designer software (Supported: Bartender UL), Virtual COM utility
- USB 2.0 FS type B C connector
- WLAN and WIFI connection
- Bluetooth enabled
- iOS compatible



### Optional Accessories

**The AC Adapter** can be plugged into the printer and charged between uses. Remains operational when charging. Charges a single battery in 6 hours

**1 and 4 Channel Battery Charger** charges a single battery in 6 hours

**Shoulder and Belt strap** available for a hands-free solution

PV4 Technical Specification

PRODUCT SPECIFICATION			PV4
Series name			PV-series
PRINTING SPECIFICATIONS			
Print Resolution			203dpi (8 dots/mm)
Method			Direct Thermal
Media setting position			Center alignment
Printer Type			Standard:Continuous, Tear-off, Dispenser    Optional: Linerless
Print speed	Printer mode		Up to 127mm/sec (5 inches/sec)
	Temperature		Ambient temperature and battery status may reduce the speed.
Print darkness			Darkness level: 0 to 30 Default: 10
Printable area			Maximum Length 400 mm (15.74") x Width 104 mm (4.09")
Size/Weight	External dimensions:		W 158 mm x D 186 mm x H 82 mm (6.23" x 7.33" x 3.23") (excluding protrusion)
	Height with cover open		W 158 mm x D 225 mm x H 127.3 mm (6.23" x 8.86" x 5.01") (excluding protrusion)
	Weight		1,090g (2.41lbs). (including battery, excluding media)
	Package dimensions		W 297 mm x L 228 mm x H 91 mm (11.69" x 8.97" x 3.58")
	Package weight		1.74 kg (3.84 lbs)
Options			Smart Battery (spare) Single battery cradle Quad battery cradle Shoulder strap
Accessories	Battery		Standard accessories
	AC Adapter		Standard accessories
	Power Cord		Standard accessories
	Belt strap		Standard accessories
	Quick guide		Standard accessories
	Installation CD		Standard accessories
	Guide disks		Paper support disk: Standard 19 mm (0.75"). Optional 12mm (0.47") included
Printer driver			Windows Driver(Euro Plus/Seagul) Linux CUPS Driver, Mac CUPS Driver OPOS Driver
Tools			Utility Program(Unified Label Utility, Net Configuration Tool) Label Artist Mobile(iOS, Android), Bartender UL
SDK			iOS SDK, Android SDK, Windows SDK (Windows XP - Windows 10), mPrint server administration tool.
MEMORY & PROCESSING			
CPU	CPU1		ARM 926 core CPU 400 MHz, Linux SDK Windows Mobile CE SDK Xamarin SDK
Onboard memory	ROM		Flash 256 MB
	RAM		SDRAM 128 MB
OPERATING CHARACTERISTICS			
Battery specifications			Smart lithium ion battery
			Voltage7.2V    Capacity : 6700mAh    48wh
	Charging method		AC adapter(Printer Charging), Single battery cradle, Quad battery cradle
			Charging Time: About 6 Hours (Adapter, Cigarette Lighter Adapter), About 10 Hours (Single/Quad battery cradle)

CONNECTIVITY			
Interface	USB		USB 2.0 FS type C connector
	Serial		RS-232 Standard mini 14pin connector
	Wireless LAN		802.11a/b/g/n (infrastructure, Ad-hoc, Wi-Fi Direct, SoftAP) TCP/IP, HTTP, DHCPv4 Security: WEP, WPA, WPA2 Encryption scheme: None, WEP (64 bits/128 bits), AES/TKIP(WPA+WPA2 mix mode-PSK, WPA2-PSK)
		Channels	1 to 13 (2.4GHz) /36 to 64,100 to 140,149 to 165 (5GHz) *Available channel varies with the country setting.
	Bluetooth		Ver.5.0 Classic + LE
			Profile: SPP,iAP2
		Easy Bluetooth Paring™ via NFC	
OPERABILITY AND SERVICEABILITY			
LCD specifications			TFT-LCD 2 inches (240 * 320, 262K Color)
Operability	Button operation		4 button: Power, Feed, Move Menu, Menu Select.
	Sensors		Black Mark Sensor (I-Mark), Gap sensor, Paper cover sensor, Label presence.
	Brightness adjustment		6 Step (might be changed later)
LED specifications			Red LED On : Charging Green LED On : Fully Charged Red LED Blinking : Error Replace or Reinstall Battery
MEDIA SPECIFICATIONS			
Media	Media thickness (Label + liner)		0.07 to 0.15 mm (0.0027" to 0.0059")
	Continuous	Length	6 to 400 mm (0.236" to 15.748")
		Width	50 to 112 mm (1.97" to 4.41")
	Tear-off	Length	6 to 400 mm (0.236" to 15.748")
		Width	50 to 112 mm (1.97" to 4.41")
	Dispenser	Length	6 to 400 mm (0.236" to 15.748")
		Width	50 to 112 mm (1.97" to 4.41")
	Media type/Media shape		Roll media (face-out wound)
			Fan-fold media
			Receipt, Linered, Continuous, Tag
	Black-Mark		Optical density 0.84 ~ 1.34
	Roll diameter/Core size		Roll media diameter
			Maximum 66 mm (2.59") Inner core
			19 mm or 12 mm (0.75" or 0.47")
FONT SPECIFICATIONS			
Built-in print fonts	Bitmap font		10 SLCS Resident Fonts, 16 BPL-Z™ Resident Fonts, 7 BPL-Z™ Resident Fonts
	Scalable font		One SLCS Resident Font, One BPL-Z™ Resident Font
	Code page support		23 Code Page, Unicode supported (UTF-8,UTF-16LE, UTF-16BE)
STANDARDS AND REGULATIONS			
Standards and regulations	Noise (EMC) regulations		CFCC, CE, SAR
	Safety regulation		UL, CB
	RoHS-2		Complies to the RoHS-2 directive restriction to use hazardous materials.
	WEEE		Compliance
	Drip/Dust-proof		IP54





[satoeurope.com](http://satoeurope.com)